



OASIS 8237 UNDERCOAT SHEEN FINISH

PRODUCT HEALTH AND SAFETY DATA

Product Reference : Oasis 8237 Undercoat Sheen Finish
Date of Issue : 14/03/2016

Issue : 1T A
Page : 1 of 9

1. IDENTIFICATION OF PREPARATION AND OF COMPANY

Full name Oasis 8237 Undercoat Sheen Finish

Manufacturer Al Gurg Paints LLC

PO Box 22334

Sharjah

United Arab Emirates

Telephone: +971 (0)65 343 919

Fax: +971 (0)65 343 983

Description: Oasis 8237 is high performance polyurethane sheen finish for application by spray or brush. Based on a two pack acrylic urethane resin system with inorganic and/or organic pigments and containing xylene, aromatic hydrocarbon and 1-methoxy-2-propyl acetate solvents.

Also, the following colours contain lead chromate pigment:-

BS381C 298 - Olive Drab	BS4800 04D45 - Crimson
BS4800 04E53 – Red	BS4800 08B29 - Vandyke
BS4800 08C35 – Cinnamon	BS4800 08E51 - Golden Yellow
BS4800 10C39 – Seaweed	BS4800 10E53 - Canary Yellow
BS4800 14E53 – Emerald	BS5252 04D44
BS5252 10	B29BS5252 12B27
BS5252 14C40 – Green	Brick Red - R4782
RAL 1003 - Signal Yellow	RAL 1004 - Gold Yellow
RAL 1005 - Honey Yellow	RAL 1021 - Cadmium Yellow
RAL 1023 - Traffic Yellow	RAL 2002 - Blood Orange
RAL 2004 - Pure Orange	RAL 2009 - Traffic Orange
RAL 3000 - Fire Red	RAL 3002 - Carmine Red
RAL 3003 - Ruby Red	RAL 3007 - Black Red
RAL 3017 – Pink	RAL 6002 - Leaf Green
RAL 6005 - Moss Green	RAL 6010 - Grass Green
RAL 6016 - Turquoise Green	RAL 6018 - Yellow Green
RAL 6021 - Pale Green	RAL 6025 - Fern Green
RAL 6031 - Bronze Green	RAL 8011 - Nut Brown
RAL 8028 - Earth Brown	Signal Red R4958UNO17
Orange - For Oranges	UNO18 Brick - For Bright/Orange Reds
UNO20 Lemon - For Bright Yellows	UNO21 Mustard - For Yellow/Light Bro
UNO27 Emerald - For Mid Greens	Yellow - R4910

2. COMPOSITION/INFORMATION ON INGREDIENTS

The following ingredients have recognised health effects or exposure limits, and are present in concentrations above the limits laid down in the Chemicals (Hazard Information and Packaging for Supply) Regulations 1994

Substance	Weight in Paint	Classification	Risk Phrases*	CAS Number
BASE				
Xylene (mixture of isomers)	10-25%	Xi	R38	1330-20-7
		Xn	R20/21	
Mesitylene	2.5-10%	Xi	R37	108-67-8
Ethylbenzene	2.5-10%	Xn	R20	100-41-4
Propylbenzene	<2.5%	Xi	R37	103-65-1
Base (for colours containing lead chromate):				
Lead Chromates	>1%		R33	7758-97-6
		Carc. Cat. 3	R40	
		Repr. Cat. 1	R61	
		Repr. Cat. 3	R62	
Xylene (mixture of isomers)	10-25%	Xi	R38	1330-20-7
		Xn	R20/21	
Mesitylene	2.5-10%	Xi	R37	108-67-8
Ethylbenzene	2.5-10%	Xn	R20	100-41-4
Propylbenzene	<2.5%	Xi	R37	103-65-1
ADDITIVE				
Xylene (mixture of isomers)	2.5-10%	Xi	R38	1330-20-7
		Xn	R20/21	
1-methoxy-2-propyl acetate	10-25%	Xi	R36	283-152-28
Aliphatic polyisocyanate	>50%	Xi	R43	28182-81-2
Ethylbenzene	2.5-10%	Xn	R20	100-41-4
Mesitylene	<2.5%	Xi	R37	108-67-8

*For full details of R-phrases, see Section 16.

3. HAZARDS IDENTIFICATION

This material has been assessed under the Chemicals (Hazard Information and Packaging for Supply)

Regulations 1994 and has been classified as follows :-

Base:		R10	Flammable.
	Xn	R20	Harmful by inhalation.
Base (with lead chromate):	Xn	R10	Flammable.
		R33	Danger of cumulative effects.
	Carc. Cat. 3	R40	Possible risk of irreversible effects
	Repr. Cat. 1	R61	May cause harm to the unborn child
	Repr. Cat. 3	R62	Possible risk of impaired fertility
Additive:		R10	Flammable.
	Xn	R20	Harmful by inhalation.
	Xi	R43	May cause sensitisation by skin contact.

4. FIRST-AID MEASURES

In all cases of doubt, or where symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

- Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.
- Eye contact** Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- Skin contact** Remove contaminated clothing. Wash skin thoroughly with soap and water, or use a proprietary skin cleanser. Do NOT use solvents or thinners.
- Ingestion** If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
-

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Use alcohol resistant foam, carbon dioxide, dry powder or water spray/mist. Do NOT use water jet.

Recommendations

Fire will produce dense black smoke containing hazardous products of combustion (see Section 10). Exposure to decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire-fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises: water (45 parts by volume)/ ethanol or isopropanol (50 parts)/ concentrated (d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/ water (95 parts). Add the same decontaminant to any residues and allow to stand for several days in a non-sealed container until no further reaction occurs. Once this stage is reached, close the container and dispose of in accordance with the waste regulations (see Section 13). Do not allow to enter drains or water courses. Clean preferably with a detergent; avoid the use of solvents..

7. HANDLING AND STORAGE

Handling

Vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid concentrations higher than the occupational exposure limits.

Additionally the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Keep the container tightly closed. Exclude sources of heat, sparks and open flame. Non-sparking tools should be used.

Required air quantity to ventilate to 10% of the LEL. 155 m³/ltr

The above figure is given as a guide only. Ventilation and extraction must be arranged so that all parts of the workplace are properly ventilated i.e. there are no recesses or pockets where high vapour concentrations are allowed to build up.

If there is any doubt about the adequacy of the ventilation/extraction of solvent vapour, regular monitoring of confined workplaces should be carried out.

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in areas of storage and use.

For personal protection, see Section 8.

Never use pressure to empty; the container is not a pressure vessel.

Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards.

	Base	Additive	Composite
20 litre unit	26 kg	2.0 kg	25 - 27 kg
5 litre unit	6.52 kg	1.0 kg	6.5 - 7 kg

Storage

Although the storage of this product is not subject to specific statutory requirements, the principles contained in the HSE guidance note Storage of Flammable Liquids in Containers, should be observed.

Observe the label precautions. Store between 5°C and 35°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are open should be properly re-sealed and kept upright to prevent leakage.

The principles contained in the HSE guidance note Storage of Packaged Dangerous Substances should be observed when storing this product. Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn (see 'Personal Protection' below).

Exposure Limits

Occupational Exposure Standards and/or Maximum Exposure Limits have been established by the Health and Safety Commission or recommended by the supplier for certain of the ingredients. OELs are taken from the current version of EH40 except those marked 'Sup', which are assigned by the supplier of the substance.

Substance	Occupational Exposure Limits		Notes
	8 hr TWA¹	15 min STEL²	
1-methoxy-2-propyl acetate	100ppm(OES)		Sup
Ethylbenzene	100ppm(OES)	125ppm(OES)	
Isocyanates	0.02mg/m ³ (MEL)	0.07mg/m ³ (MEL)	
Lead compounds	0.15mg/m ³ (MEL)		
Mesitylene	25ppm(OES)		
Xylene (mixture of isomers)	100ppm(OES)	150ppm(OES)	Skin
	¹	Long term exposure limit - 8 hour time weighted average	
	²	Short term exposure limit - 15 minute reference period	
	³	There is a risk of absorption through unbroken skin	
	OES	Occupational exposure standard	

Further guidance on OES/MEL and the assessment of occupational exposure to harmful materials, including mixed exposures, is given in HSE Guidance Note EH40.

Personal Protection

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet requirements of the COSHH Regulations.

Respiratory Protection Air-fed respiratory protective equipment should be worn when this product is sprayed if the exposure of the sprayer or other people nearby cannot be controlled to below the Occupational Exposure limits and engineering controls and methods cannot reasonably be improved.

Dry-sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Hand Protection When skin exposure may occur, advice should be sought from glove suppliers on appropriate types.

Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

Eye Protection Eye protection designed to protect against liquid splashes should be worn.

Skin Protection Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleanser.

9. PHYSICAL PROPERTIES

Physical State	Viscous liquid
Odour	Characteristic odour
Colour	Various
Density	1.40 g/cm ³
Viscosity Base	4.6 -8 poise DR at 25°C
Viscosity Additive	32-44 Sec B2 at 25°C
Flash Point base	28°C
Flash Point Additive	32°C
Volatile Organic Content	443 g/ltr
Explosion Limit - lower	1.0%
Water Solubility	Immiscible

10. STABILITY AND REACTIVITY

Stable under the recommended storage and handling conditions (see Section 7).

In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced.

Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.

Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the renal and central nervous systems. Symptoms include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eye may cause irritation and reversible local damage.

Ingestion may result in the following effects: sore throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea. Other effects may be as described for exposure to vapours.

Product Reference : Oasis 8237 Undercoat Sheen Finish
Date of Issue : 14/03/2016

Issue : 1T A
Page : 6 of 9

Increased incidences of lung cancer have been identified in the chromate manufacturing industry. Epidemiological studies have shown that where lead chromates alone were manufactured there were no cancer excesses.

Animal studies have shown that some insoluble chromates are carcinogenic but the data does not extend to lead chromate pigments. There is no evidence of a risk of lung cancer arising from the use of lead chromate containing products.

Epidemiological data shows an association between elevated maternal blood lead levels and developmental effects in the offspring. Following the introduction of the criteria for Toxic ton reproduction hazard classification the EC has classified all lead compounds as causing developmental toxicity in humans. Lead chromate, although of relatively low solubility and bioavailability, is included in this classification.

Based on the properties of the isocyanate content of this product, respiratory exposure may cause acute irritation and/or sensitisation of the respiratory system, resulting in asthmatic symptoms, wheezing and a tightness of the chest. Sensitised persons may subsequently show asthmatic symptoms when exposed to airborne concentrations of isocyanates well below the occupational exposure limit. Repeated exposure may lead to permanent respiratory disability.

12. ECOLOGICAL INFORMATION

There is no data available on the product itself.

The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains or water courses, or dispose of where ground or surface waters may be affected.

Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet, advice should be obtained from the Environment Agency whether the special waste regulations apply.

14. TRANSPORT INFORMATION

Transport within the user's premises

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport Classification

Base:

Transport Details

Class : 3
Sub Hazard : -
Packing Group : III

Proper Shipping Name : Paint
UN Number : 1263

Ensure drivers have adequate training.

For International Road/Rail

Chemical Name : Paint

Item Number : 31°(c)

Trem Card : 30G35

For Sea Transport

Product Reference : Oasis 8237 Undercoat Sheen Finish
Date of Issue : 14/03/2016

Issue : 1T A
Page : 7 of 9

Marine Pollutant : No
EmS : 3-05
MFAG : 310

Additive:

Transport Details

Class : 3
Sub Hazard : -
Packing Group : III

Proper Shipping Name : Paint
UN Number : 1263

Ensure drivers have adequate training.

For International Road/Rail

Chemical Name : Paint
Item Number : 31°(c)
Trem Card : 30G35

For Sea Transport

Marine Pollutant : No
EmS : 3-05
MFAG : 310

This information does not apply to carriage by air. Please contact the Export Department of Al Gurg Paints LLC if transport by air is required.

15. REGULATORY INFORMATION

The product has been classified and labelled for supply in accordance with the CHIP 2 regulations as follows:-

For all colours except those listed in Section 1 as containing lead chromate:-

Base:

Symbols:



IRRITANT

Named Substances: Xylene (mixture of isomers)

Warning label phrases: Flammable.

Irritating to eyes and skin

May cause sensitisation by skin contact.

Do not breathe vapour/spray.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wear suitable protective clothing and gloves

In case of insufficient ventilation, wear suitable respiratory equipment

Base for colours containing lead chromate (see Section 1):

Base:

Symbols:



Named Substances: Lead Chromates
Xylene (mixture of isomers)

Warning label phrases: Contains lead. Should not be used on surfaces that are liable to be chewed or sucked by children
Contains epoxy constituents. See information supplied by the manufacturer.
Restricted to professional users.
Flammable.
Danger of cumulative effects.
Possible risk of irreversible effects
May cause sensitisation by skin contact.
May cause harm to the unborn child
Possible risk of impaired fertility
Do not breathe vapour/spray.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Wear suitable protective clothing and gloves
During spraying wear air-fed respiratory protective equipment.

Additive:

Symbols:



HARMFULL

Named Substances: Aliphatic polyisocyanate

Warning label phrases: Flammable.
Danger of cumulative effects.
Possible risk of irreversible effects
May cause sensitisation by skin contact.
May cause harm to the unborn child
Possible risk of impaired fertility
Do not breathe vapour/spray.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Wear suitable protective clothing and gloves
During spraying wear air-fed respiratory protective equipment.

The information contained in this data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation.

The provisions of the Health and Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

16. OTHER INFORMATION

Full details of R-phrases are as follows:-

Full details of R-phrases are as follows:-

R20 Harmful by inhalation.
R20/21 Harmful by inhalation and in contact with skin.
R33 Danger of cumulative effects.
R36 Irritating to eyes
R37 Irritating to respiratory system
R38 Irritating to skin
R40 Possible risk of irreversible effects
R43 May cause sensitisation by skin contact.
R61 May cause harm to the unborn child
R62 Possible risk of impaired fertility

Full details of the hazard classifications are as follows:-

Repr. Cat. 1 Toxic for reproduction - Category 1
Repr. Cat. 3 Toxic for reproduction - Category 3
Carc. Cat. 3 Carcinogenic - Category 3

Further information about hazard classifications can be found in the Approved Guide to the Classification and Labelling of Substances and Preparations Dangerous for Supply.

The information in this data sheet is provided in accordance with the requirements of the Chemicals (Hazard Information and Packaging for Supply) Regulations 1994.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Further information and relevant advice can be found in:-

The Chemicals (Hazard Information and Packaging for Supply) Regulations 1994 (SI 1994:3247)

Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972 (SI 1972:917)

Control of Lead at Work Regulations 1980 (SI 1980:1248)

Control of Substances Hazardous to Health Regulations 1988 (SI 1988:1657)

Manual Handling Operations Regulations 1992 (SI 1992:2793)

Environmental Protection (Duty of Care) Regulations 1992 (SI 1992:2839)

Occupational Exposure Limits, EH40

Your Health and 2-pack spray paints, MS(B)8

Surveillance of people exposed to health risks at work (ISBN 0 11 885574 3)

The storage of flammable liquids in containers, HS(G)51

Storage of Packaged Dangerous Substances, HS(G)71

The Approved Guide to the Classification and Labelling of Substances and Preparations Dangerous for Supply (Second Edition), L63

The Approved Supply List, L76