

TECHNICAL DATA

PRODUCT: OASIS TRUWOOD PU THINNER # 1105

Description	:	Oasis Truwood PU Thinner # 1105 is a mix of aromatic hydrocarbon, ester & ketone. It is suitable for polyurethane based sealer, primer, clear and pigmented topcoat.
Flash Point	:	10°C
Specific Gravity (Kg/Ltr)	:	0.87 ± 0.03
Colors	:	Clear Transparent
Pack Size	:	190 Ltr. , 18 Ltr. , 3.78 Ltr.
Application Notes	:	Recommended up to 50 % by volume according to type of equipment and application method.
Application Methods	:	Suitable for Conventional, Airless spray or brush application

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION (READ THIS SECTION BEFORE USE)

- Flammable. Keep away from sources of ignition. Do not smoke.
- Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE. Refer to your COSSH Assessment.
- When applying paint it is advisable to wear suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Remove splashes from skin: use soap and water or a recognized skin cleaner.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into wadis, drains or watercourses.
- Contains no added mercury.

*This data is subject to change without notice. Please ensure you have the latest copy by checking with our Customer Service Department.

April - 2015
Issue 1: Revision:0



For further information please contact –
AL GURG PAINTS L.L.C
Head Office & Factory – P.O. Box 22334,
Sharjah, U.A.E
Tel : (+971)6-5343919 Fax : (+971)6 5343983
E-mail : enquiries@agp.ae
Web : www.aqlpuae.com