



TECHNICAL DATA

PRODUCT: OASISFLOOR 8766

Description	:	Oasisfloor 8766 is two component penetrating epoxy sealer		
Recommended use	:	Penetrating sealer for concrete, wood and other porous substrates Due to good penetration power into wood, paints or varnish applied over will last longer		
Volume Solids (%)	:	40±3%		
Flash Point	:	Base 32°C	Additive 32 °C	
Specific Gravity (Kg/Ltr)	:	0.97 (Mixed)		
Colours	:	Clear		
Pack Size	:	4Ltrs and 20 Ltrs		
Mixing Ratio	:	3 parts base to 1 part additive by volume		
Theoretical Spread Rate	:			
@ Dry Film Thickness	:	40 µm	50 µm	60µm
@ Wet Film Thickness	:	100 µm	125 µm	150 µm
		It should be noted that the actual spread rate will vary depending upon the type of substrate coated and the method of application chosen. If the surface to be coated is excessively rough or porous, the spread rate may be significantly reduced. When treating such surfaces, practical tests should be carried out prior to the onset of full scale painting		
Drying Time @ temperature	:	25°C	35°C	
To Touch	:	2.5 hrs	1hr	
To Overcoat (Minimum)	:	18 Hrs	10Hrs	
		These figures are given as a guide only. Factors such as air movement and humidity must also be considered.		
Cleanser or Thinner	:	Thinner # 5		
Pot Life	:	23°C 4 hours	35°C 2 hours	
Recommended top coats	:	May be overcoated with any of the PU range of products as well as other high performance epoxies systems provided that the surfaces to be coated have been suitably cleaned. To achieve optimum adhesion, overcoating should be undertaken within 7 days at 23°C or within 4 days at 35°C.		
Application Notes	:	Dilution up to 5-10 % by volume may be required according to type of equipment and application method.		
Application Methods	:	Conventional Spray, Roller, Brush		
Surface Preparation	:	Ensure surfaces to be coated are dry and free from all traces of surface contaminants		

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION (READ THIS SECTION BEFORE USE) SOLVENT BASED PAINT PRODUCT

- Flammable. Keep away from sources of ignition. Do not smoke.
 - Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE. Refer to your COSSH Assessment.
 - When applying paint it is advisable to wear suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 - Remove splashes from skin : use soap and water or a recognised skin cleaner.
 - Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into wadis, drains or watercourses.
 - Contains no added mercury.
- *This data is subject to change without notice. Please ensure you have the latest copy by checking with our Customer Service Department.

March 2013
Issue 1: Revision:0



For further information please contact –
AL GURG PAINTS L.L.C
 Head Office & Factory – P.O. Box 22334,
 Sharjah, U.A.E
 Tel : (+971)6-5343919 Fax : (+971)6 343983
 E-mail : enquiries@agp.ae
 Web : www.aqlpuae.com