

TECHNICAL DATA

Description	:	OASIS 8500 CLEANISING SOLUTION
Material Type	:	Solvent based water emulsifiable degreasing solution.
Recommended Use	÷	Suitable for removal of dirt,oil or grease from metal surfaces, machinery and other surfaces. Oasis 8500 solution may be used for degreasing painted surfaces. However, certain types of coating may be softened or affected by Oasis 8500 cleansing solution and it is recommended that a test be undertaken on a small area before proceeding with application to larger areas. Suitable for cleaning paint brushes and rollers. Oasis 8500 Cleansing Solution is not suitable for use a 'Quick Break' solvent degreasant for enclosed systems.
Recommended Application Method	:	Apply to the surface by brush or cloth and allow to stand for few minutes. Rinse off thoroughly with clean fresh water ensuring that any residual film of grease is entirely removed from the surface prior to painting. If the supply of fresh water is restricted wipe off with a water dampened cloth.
Flash Point	:	39°C
Specific Gravity (Kg/Ltr)	:	0.82 Kg/Litre
V.O.C.	:	720 gram/Litre
Colours	:	Amber Liquid.
Pack Size	:	5 Litreand 25 Litre Unit.
Shelf Life	:	Minimum 2 years
Package	:	Single Component Material
% Solid by Volume	:	10 +/- 1% (ASTM-D2697-91)

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION (READ THIS SECTION BEFORE USE) SOLVENT BASED PAINT PRODUCT

- Flammable. Keep away from sources of ignition. Do not smoke.
- Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When be suitable for the purpose and meet an appropriate standard approved by the HSE. Refer to your COSSH Assessment.
- When applying paint it is advisable to wear suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 - Remove splashes from skin: use soap and water or a recognised skin cleaner.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into wadis, drains or

Additional Notes

Contains no added mercury.
*This data is subject to change without notice. Please ensure you have the latest copy by checking with our Customer Service Department.

April 2016 Issue 1: Revision:1





further information please contact -AL GURG PAINTS L.L.C Head Office & Factory - P.O. Box 22334, Sharjah, U.A.E

Numerical values quoted for physical data may vary slightly from batch to batch.

Tel: (+971)6-5343919 Fax: (+971)6 343983

E-mail: enquiries@agp.ae Web: www.aglpuae.com