

## Oasis Acrylic Primer (W.B)

Description:	Oasis Acrylic Primer (Water Based) is an exterior coating which is alkali resistant, high quality special acrylic emulsion primer for masonry and plaster surfaces. It has good penetrating and adhesion properties and provides good anchor to the subsequent coats.
Recommended usage:	Recommended for exterior cement plaster, concrete and brick works. Oasis Acrylic Primer (W.B) can also be used on wood, asbestos, and gypsum.
Pack Size:	1 USG [3.78L], 5 USG [18.9L]
Physical properties:	
Finish:	Smooth and Matt
Colour range:	WHITE {Pastel shades possible for Large Quantity requirements}
Volume (solids %):	36± 2%
Specific gravity:	1.42 ± 0.03
Theoretical spread rate:	12.0 m <sup>2</sup> /litre at 30 microns DFT
Flash point:	Non-flammable
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will vary according to temperature, humidity and film thickness and will be affected accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Surface dry:	1-2 hours
Recoat window:	4 -6 hours
	The given data is meant to be considered as guidelines only. The actual drying time before recoat may vary according to atmospheric conditions at site.
Recommended System:	<ul style="list-style-type: none"> <li>• On new and bare surface prime with 1 coat Oasis Acrylic Primer (W.B).</li> <li>• Apply 2 coats of Oasis Stucco.</li> <li>• 2 coats Oasis Trumastic Products or Trushield Products.</li> </ul> <p>For best colour consistency use sufficient tinted / coloured paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.</p>
Surface Preparation:	<ul style="list-style-type: none"> <li>• Surfaces must be clean, completely dry and free from defects, oil, wax, grease and dust. Any chalking or any loose flaking material must be removed by scraping or brushing with a stiff bristle brush.</li> <li>• Use suitable filler for smaller cracks and holes.</li> </ul>
Application:	<ul style="list-style-type: none"> <li>• Stir thoroughly before use.</li> <li>• Use brush, roller or spray.</li> <li>• Ready to use. [Depending on site conditions the paint can be diluted with maximum 1 part clean water to 10 parts paint.]</li> <li>• Avoid painting in direct sunlight.</li> <li>• Store the paint in a cool place.</li> </ul>



## Oasis Acrylic Primer (W.B)

Advantages:	Excellent alkali resistance, excellent adhesion to surfaces, good penetration, excellent base coat for subsequent coats, suitable for exterior surfaces, special acrylic based binder, good coverage.
Health, Safety and Environmental Information:	<ul style="list-style-type: none"><li>• Keep out of the reach of children.</li><li>• If swallowed, seek medical advice immediately</li><li>• Avoid contact with skin and eyes</li><li>• Do not empty into drains</li><li>• Ensure good ventilation during application and drying.</li><li>• Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.</li></ul>

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

