

TECHNICAL DATA



PRODUCT : OASIS ALUMINIUM PAINT (G.P.)

Description	: A general purpose oil or alkyd resin based aluminium paint for use on its own or over an alkyd system giving a glossy, weather resistant metallic finish.
Volume Solids (%)	: 31 ± 2
Flash Point	: 40°C.
Specific Gravity (kg/ltr)	: 0.94 ± 0.02
Colours	: Aluminium.
Pack Size	: 1 US Gallon and 5 US Gallon.
Theoretical Spread Rate (m ² /ltr)	: 12.8
@ Dry Film Thickness	: 25 microns.
@ Wet Film Thickness	: 80 microns.
	<i>Spreading rates are calculated and due allowance for loss and wastage should be made.</i>
Drying Time to Touch	: 2 to 3 hours.
Drying Time to Overcoat	: 12 hours.
Cleanser or Thinner	: Oasis G.P. Thinner.
Application Notes	: Can be applied on most surfaces direct by brush, roller, conventional or airless spray.
Application Methods	: Airless or conventional spray, brush or roller.
Surface Preparation	: Ensure surface is dry and free of oil, grease and rust, dust, loose particles, powder paint etc.

SYSTEM INFORMATION

Steelwork

2 to 3 coats Oasis Aluminium paint (G.P.)

OR

1 coat Oasis Redox Primer 53

1 coat Oasis Undercoat

1 coat Oasis Aluminium Paint (G.P.)

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION

(READ THIS SECTION BEFORE USE)

SOLVENT BASED PAINT PRODUCT

- Flammable. Keep away from sources of ignition. No smoking.
- Contains white spirit. Work only in areas of good ventilation. Inside, always keep doors and windows fully open during application and drying. When applying by brush or roller to large surface areas inside or using in small confined spaces, the wearing of air supplied breathing equipment will normally be necessary. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly.
All respiratory equipment must be suitable for the purpose and meet an appropriate standard.
- When applying paint it is advisable to wear suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Remove splashes from skin, use soap and water or a recognised skin cleaner.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty contents into wadis, drains or watercourses.
- Contains no added lead.

*This data is subject to change without notice. Please ensure you have the latest copy by checking with our Customer Service Department

AL GURG LEIGH'S PAINTS L.L.C.

P.O. Box 22334, Sharjah, U.A.E. Tel.: (+971) 6 5343919, Fax: (+971) 6 5343983
P.O. Box 70024, Abu Dhabi, U.A.E. Tel.: (+971) 2 6723329, Fax: (+971) 2 6726671
E-mail: Enquiries@algurgleighpaint.ae



Cert. Regn. No.: 0410021840