

Oasis Epoxy Filler

Description:	Oasis Epoxy Filler [Solvent Free] is two pack non shrink epoxy mastic designed to fill irregularities in concrete and steel. Supplied as material with 100% solids which results in no shrinkage after application.
Recommended Usage:	For Steel and concrete surfaces.
Caution:	Not recommended for surfaces having loose and powdery profiles.
Pack Size:	1.5 Kg & 6 Kg
Physical properties:	
Finish:	Smooth and Matt
Colour range:	Off-White
Volume (Solids. %):	100%
Specific gravity:	1.60 ± 0.03 (Mixed Paint)
Theoretical spread rate:	Depends on the cavities and imperfections on surface.
Flash point:	Above 60°C
Mixing Ratio:	7:1 by Weight
Pot Life:	1 Hour
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will vary according to temperature, humidity and film thickness and will be affected accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Surface dry:	1 hour
Recoat window:	Minimum 16 hours
Maximum Over coating time:	5 days
	The given data must be considered as guidelines only. The actual drying time before recoat may vary according to atmospheric conditions at site.
Recommended System:	<ul style="list-style-type: none"> • Appropriate Primer • Oasis Epoxy Filler (to fill the cracks and imperfection) • Appropriate Oasis Finish • For best colour consistency use sufficient tinted / coloured paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.
Surface Preparation:	<ul style="list-style-type: none"> • Surfaces must be sound, clean, completely dry and free from defects, oil, wax, grease and dust. Any loose or flaking material must be removed by scraping or brushing with a stiff bristle brush. • Use suitable filler for smaller cracks and holes.
Application:	<ul style="list-style-type: none"> • Stir thoroughly before use • Use Putty Knife. • Ready to use • As the material is solvent free; it has a short pot life. Mix thoroughly only the quantity to be used and is to be applied within the curing period. • Avoid painting in direct sunlight • Store the paint in a cool place.



Oasis Epoxy Filler

Health, Safety and

Environmental Information:

- Solvent based and flammable
- Keep out of the reach of children.
- If swallowed, seek medical advice immediately.
- Avoid contact with skin and eyes
- Do not empty into drains
- Ensure good ventilation during application and drying.
- Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

