

Oasis Matt Enamel

Description:	Oasis Matt Enamel is a general purpose alkyd based enamel for wooden and steel surfaces. It is resistant to cracks and abrasions and has good adhesion whilst being washable.
Recommended Usage:	It is used as a general purpose interior finish for wood and steel surfaces. It has good adhesion to anti-corrosive primer and earlier paint system.
Caution:	Avoid using directly on cementitious surfaces.
Pack Size:	1 litre, 1 USG [3.78L], 5 USG [18.9L]
Physical properties:	
Finish:	Smooth and Matt
Colour range:	Refer Oasis fan deck
Volume (Solids. %):	50 ± 2%
Specific gravity:	1.44 ± 0.03
Theoretical spread rate:	16.6 m ² /litre at 30 microns DFT
Flash point:	38°C
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will vary according to temperature, humidity and film thickness and will be affected accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Surface dry:	1-12 hours
Recoat window:	12 hours
The given data must be considered as guidelines only. The actual drying time before recoat may vary according to atmospheric conditions at site.	
Surface Preparation:	<ul style="list-style-type: none"> Surfaces must be sound, clean, completely dry and free from defects, oil, wax, grease and dust. Any chalking or any loose or flaking material must be removed by scraping or brushing with a stiff bristle brush. Use suitable filler for smaller cracks and holes.
Recommended System:	<ul style="list-style-type: none"> On previously painted surfaces in good condition and where similar colours are used, 1 coat may be sufficient. On new and bare steel apply 1 coat of Oasis Red-oxide Primer. For wood surface, apply one coat of Oasis Wood Primer Apply one coat of Oasis Undercoat depending on surface condition. Apply 2 coats of Oasis Matt Enamel. <p>For best colour consistency use sufficient tinted / coloured paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.</p>
Application:	<ul style="list-style-type: none"> Stir thoroughly before use Use brush, roller or spray. Ready to use* [Depending on site conditions the paint can be diluted with maximum 1 part Oasis GP Thinner / Oasis Thinner No: 1 to 10 parts paint.] Avoid painting in direct sunlight Store the paint in a cool place.



Oasis Matt Enamel

Advantages:

- Washable, Excellent levelling, opacity and adhesion properties.

Health, Safety and

- Solvent based product and flammable

Environmental Information:

- Keep out of the reach of children.
- If swallowed, seek medical advice immediately.
- Avoid contact with skin and eyes
- Do not empty into drains
- Ensure good ventilation during application and drying.
- Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Oasis Enamels

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

