## **TECHNICAL DATA**



## PRODUCT: OASIS Q.D. VARNISH CLEAR

Description	:	Oasis Q.D Varnish Clear is a special alkyd resin based glossy clear coating specially developed for oil country tubular. The coating is user friendly and quick drying, once applied provides corrosion protection during storage. Being its excellent clearity allows better visibility to existing colour codes and markings on the tubes.
Volume Solids (%)	:	25±3%
Flash Point	:	Above 27℃
Specific Gravity (Kg/Ltr)	:	0.96±2%
Colours	:	Clear
Pack Size	:	1 USG and 5 USG
Theoretical Spread Rate (m²/Ltr) @ Dry Film Thickness @ Wet Film Thickness	:	10 m <sup>2</sup> /Ltr 15 μm 60 μm Spreading rates are calculated and due allowance for loss and wastage should be made.
Drying Time @ temperature To Touch	:	15℃25℃35℃20min10 min5 minThese figures are given as a guide only. Factors such as air movement and humidity must also be considered.
Cleanser or Thinner	:	Thinner # 3 or 2
Application Notes	:	Dilution according to type of equipment and application method
Application Methods	:	Conventional, airless spray, Brush or Roller
Surface Preparation	:	Ensure surface is dry and free of oil, grease, rust, dust, loose particles, powder paint, etc.
Shelf Life	:	Minimum 1 year

## SAFETY, HEALTH & ENVIRONMENTAL INFORMATION - (READ THIS SECTION BEFORE USE)

## SOLVENT BASED PAINT PRODUCT

Flammable. Keep away from sources of ignition. Do not smoke.

Work only in areas of good ventilation. When used indoors always keep doors and windows fully open during application and drying. When applying for short periods only, a suitable cartridge mask may be worn provided the filter is changed regularly. All respiratory equipment must be suitable for the purpose and meet an appropriate standard approved by the HSE. Refer to your COSSH Assessment

When applying paint it is advisable to wear suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove splashes from skin : use soap and water or a recognised skin cleaner.

Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook. Do not empty into wadis, drains or watercourses. Contains no added mercury.

\*This data is subject to change without notice. Please ensure you have the latest copy by checking with our Customer Service Department.

September 2012 Issue 1: Revision: 1





For further information please contact -AL GURG PAINTS L.L.C Head Office & Factory - P.O. Box 22334, Sharjah, U.A.E Tel : (+971)6-5343919 Fax : (+971)6-5343983 E-mail : enquiries@agp.ae Web : www.aglpuae.com