

## Oasis Stucco

Description:	Oasis Stucco is an emulsion based high solid putty/filler. It is a thick homogeneous paste and provides excellent body filling and coverage. Oasis Stucco has excellent sandability and can achieve smooth surface for subsequent coats covering light undulations.
Recommended Usage:	Oasis Stucco is recommended as putty for concrete, plaster, gypsum, masonry works and MDF surfaces. It is always to be used as an undercoat for interior applications only.
Pack Size:	1 USG [3.78L], 5 USG [18.9L]
Physical properties:	
Finish:	Matt and Smooth
Colour range:	White
Volume (Solids %):	55 ± 2%
Specific gravity:	1.71 ± 0.05
Theoretical spread rate:	5-7m <sup>2</sup> /litre depending on the surface
Flash point:	Non-flammable
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will vary according to temperature, humidity and film thickness and will be affected accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Surface dry:	45 to 60 minutes
Recoat Window:	3-4 hours  The given data must be considered as guidelines only. The actual drying time before recoat may vary according to atmospheric conditions at site.
Recommended System:	<ul style="list-style-type: none"> <li>• On new and bare surfaces prime with 1 coat Oasis Acrylic Primer (W.B) or Oasis PVA Primer(W.B)</li> <li>• 2 coats Oasis Stucco.</li> <li>• 2 coats of Oasis recommended system</li> </ul> <p>For best colour consistency use sufficient tinted / coloured paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.</p>
Surface Preparation:	<ul style="list-style-type: none"> <li>• Surfaces must be sound, clean, completely dry and free from defects, oil, wax, grease and dust. Any chalking or any loose or flaking material must be removed by scraping or brushing with a stiff bristle brush.</li> <li>• Use suitable filler for smaller cracks and holes.</li> </ul>
Application:	<ul style="list-style-type: none"> <li>• Stir thoroughly before use</li> <li>• Use Putty knife, Glazing knife, and scrapper.</li> <li>• Ready to use* [Depending on site conditions the paint can be diluted up to a maximum of 1 part clean water to 10 parts paint]</li> <li>• Avoid painting in direct sunlight</li> <li>• Store the paint in a cool place.</li> </ul>
Advantages:	Excellent sandability ,recoatability, body filling, coverage and easy application



## Oasis Stucco

Health, Safety and  
Environmental Information:

- Keep out of the reach of children.
- If swallowed, seek medical advice immediately.
- Avoid contact with skin and eyes
- Do not empty into drains
- Ensure good ventilation during application and drying.
- Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

