

Trumastic Luxury Matt

Description:	Trumastic Luxury Matt is a premium superior quality acrylic copolymer based highly washable emulsion paint for interior surfaces. It has excellent alkali and scrub resistance. Additionally it has inherent anti chalking properties.
Recommended Usage:	Trumastic Luxury Matt is suitable for decorative application on interior surfaces like concrete, plaster brickwork, masonry, gypsum board, asbestos, and wooden surfaces.
Pack Size:	1 litre, 1 USG [3.78L], 5 USG [18.9L]
Physical properties:	
Finish:	Smooth and Matt
Colour range:	Refer Oasis Fan deck
Volume (Solids %):	44 ± 2%
Specific gravity:	1.38 ± 0.05
Theoretical spread rate:	14.5 m ² /litre at 30 microns DFT
Flash point:	Non-flammable
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will vary according to temperature, humidity and film thickness and will be affected accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Surface dry:	1 hour
Recoat window:	2-4 hours
Full dry:	24 hours
	The given data is meant to be considered as guidelines only. The actual drying time before recoat may vary according to atmospheric conditions at site.
Surface Preparation:	<ul style="list-style-type: none"> • Surfaces must be sound, clean, completely dry and free from oil, wax, grease and dust. Chalk, dust and any loose or flaking material must be removed by scraping or brushing with a stiff bristle brush. • Use suitable filler for smaller cracks and holes.
Application:	<ul style="list-style-type: none"> • Stir thoroughly before use • Use brush, roller or spray. <p>Ready to use* (Depending on site conditions the paint can be diluted with maximum 1 part clean water to 10 parts paint)</p> <ul style="list-style-type: none"> • Avoid painting in direct sunlight • Store the paint in a cool place.
Recommended System:	<ul style="list-style-type: none"> • On previously painted surfaces in good condition, where similar colours are used, 1 coat may be sufficient. • On new and bare surfaces prime with Oasis PVA Primer or Oasis Acrylic Primer. • Apply 1-2 coats of Oasis Stucco, if needed • Apply 2 full coats of Trumastic Luxury Matt emulsion. <p>For best colour consistency use sufficient tinted / coloured paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.</p>

Trumastic Interior Emulsions



Trumastic Luxury Matt

- Independent Product Testing done:
- WASHABILITY Feature tested by Al Futtaim Exova labs.
 - Surface Spread of Flame tested by Exova Warringtonfire, UK.
-
- Health, Safety and Environmental Information:
- Keep out of the reach of children.
 - If swallowed, seek medical advice immediately
 - Avoid contact with skin and eyes
 - Do not empty into drains
 - Ensure good ventilation during application and drying.
 - Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used

Trumastic Interior Emulsions

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

