

## Trumastic Luxury Semi Gloss

Description:	Trumastic Luxury Semi Gloss is a premium quality acrylic copolymer based, emulsion paint for interior surfaces. It has excellent alkali resistance and highly washable. It provides a smooth luxurious semi-gloss finish.
Recommended Usage:	Suitable decorative coating for interior surfaces like concrete, Plaster blocks, asbestos, masonry and wooden surfaces.
Pack Size:	1 litre, 1 USG [3.78L], 5 USG [18.9L]
Physical properties:	
Finish:	Smooth and Semi-gloss
Colour range:	Refer Oasis Fan-deck
Volume (Solids %):	45 ± 2%
Specific gravity:	1.28 ± 0.03
Theoretical spread rate:	15 m <sup>2</sup> /litre at 30 microns DFT
Flash point:	Non-flammable
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will vary according to temperature, humidity and film thickness and will be affected accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Surface dry:	1 hour
Recoat window:	2-4 hours
Full dry:	24 hours
	The given data is meant to be considered as guidelines only. The actual drying time before recoat may vary according to atmospheric conditions at site.
Surface Preparation:	<ul style="list-style-type: none"> <li>• Surfaces must be clean, completely dry and free from defects, oil, wax, grease and dust. Any chalking or any loose flaking material must be removed by scraping or brushing with a stiff bristle brush.</li> <li>• Use Suitable filler for smaller cracks and holes.</li> </ul>
Application:	<ul style="list-style-type: none"> <li>• Stir thoroughly before use</li> <li>• Use brush, roller or spray.</li> <li>• Ready to use[*Depending on site conditions the paint can be diluted with maximum 1 part clean water to 10 parts paint]</li> <li>• Avoid painting in direct sunlight</li> <li>• Store the paint in a cool place.</li> </ul>
Recommended System:	<ul style="list-style-type: none"> <li>• On previously painted surfaces in good condition, where similar colours are used, 1 coat may be sufficient.</li> <li>• On new and bare surfaces prime with Oasis PVA Primer or Oasis Acrylic Primer.</li> <li>• Apply 1-2 coats of Oasis Stucco, if needed</li> <li>• To avoid delamination due to mechanical damage it is advisable for Stucco to be sealed with one coat of Oasis PVA Primer prior to applying the top coat.</li> <li>• Apply 2 full coats of Trumastic Luxury Semi Gloss emulsion.</li> </ul> <p>For best colour consistency use sufficient tinted / coloured paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.</p>



## Trumastic Luxury Semi Gloss

Independent Product Testing done:	• WASHABILITY Feature tested by Al Futtaim Exova labs.
Health, Safety and	• Keep out of the reach of children.
Environmental Information:	• If swallowed, seek medical advice immediately. • Avoid contact with skin and eyes • Do not empty into drains • Ensure good ventilation during application and drying. • Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Trumastic Interior Emulsions

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

