

## Trushield Heavytex

Description:	Trushield Heavytex is a textured emulsion paint which contains heavy duty pigments and coarse aggregates for both interior and exterior surfaces demanding excellent resistance to tough atmospheric conditions. The coating is capable of hiding hair line cracks and minor surface imperfections. Possessing excellent adhesion properties; it is very effective against fungal and mould growth whilst providing excellent alkali resistance.
Recommended Usage:	Recommended to be used as a coarse textured decorative coating for concrete plaster, prefabs, gypsum board, brick and masonry Surfaces.
Pack Size:	1 USG [3.78L], 5 USG [18.9L]
Physical properties:	
Finish:	Coarse Texture and matt
Colour range:	Limited Colour Range
Volume (Solids %):	64 ± 2%
Specific gravity:	1.81 ± 0.03
Theoretical spread rate:	1 .1 – 2.1 m <sup>2</sup> /litre depends on the texture
Flash point:	Non-flammable
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will vary according to temperature, humidity and film thickness and will be affected accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Surface dry:	1-2 hours
Recoat window:	6-8 hours
Full dry:	24 hours
	The given data is meant to be considered as guidelines only. The actual drying time before recoat may vary according to the atmospheric conditions at site.
Surface Preparation:	<ul style="list-style-type: none"> <li>• Surfaces must be clean, completely dry and free from defects, oil, wax, grease and dust. Any chalking or any loose flaking material must be removed by scraping or brushing with a stiff bristle brush.</li> <li>• Use suitable filler for smaller cracks and holes.</li> </ul>
Application:	<ul style="list-style-type: none"> <li>• Stir thoroughly before use</li> <li>• Use roller or hopper gun for spray.</li> <li>• Ready to use [*Depending on site conditions the paint can be diluted with maximum 1 part clean water to 10 parts paint].</li> <li>• Avoid painting in direct sunlight.</li> <li>• Store the paint in a cool place.</li> </ul>
Recommended System:	<ul style="list-style-type: none"> <li>• On new and bare surfaces prime with Oasis Acrylic Primer or Oasis Tex Primer.</li> <li>• Apply 1 coats of Oasis Trushield Heavytex texture.</li> <li>• Apply recommended suitable Topcoat (if required and optional)</li> </ul> <p>For best colour consistency use sufficient tinted / coloured paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.</p>

Trushield Exterior Emulsions



## Trushield Heavytex

Health, Safety and

Environmental Information:

- Keep out of the reach of children.
- If swallowed, seek medical advice immediately.
- Avoid contact with skin and eyes.
- Do not empty into drains.
- Ensure good ventilation during application and drying.
- Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Trushield Exterior Emulsions

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

