

## Trushield Heritage Classique

Description:	Trushield Heritage Classique is 100% pure acrylic emulsion based groove textured paint with excellent durability. It has high quality light aggregates designed to give it an antique but classical floral look. It is resistant to UV radiation, weather, alkali and carbon dioxide pollution.
Recommended Usage:	Recommended to be used as a groove textured decorative design coating for concrete plaster, prefabs, gypsum board, brick and masonry Surfaces.
Pack Size:	1 USG [3.78 L], 5 USG [18.9 L]
Physical properties:	
Finish:	Special Antique Finish
Colour range:	Limited Range
Volume (Solids. %):	65 ± 3%
Specific gravity:	1.88 ± 0.03
Theoretical spread rate:	0.6 – 1.4m <sup>2</sup> /litre depends on the texture and design
Flash point:	Non-flammable
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will vary according to temperature, humidity and film thickness and will be affected accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Touch dry:	2-3 hours
Recoat:	6-8 hours
Full dry:	24-48 hours
	The given data must be considered as guidelines only. The actual drying time before recoat may vary according to atmospheric conditions at site.
Surface Preparation:	<ul style="list-style-type: none"> <li>Surfaces must be sound, clean, completely dry and free from oil, wax, grease and dust. Chalk, dust and any loose or flaking material must be removed by scraping or brushing with a stiff bristle brush.</li> <li>Use suitable filler for smaller cracks and holes.</li> </ul>
Application:	<ul style="list-style-type: none"> <li>Stir thoroughly before use.</li> <li>Use Trowel.</li> <li>Ready to use [*Depending on site conditions the paint can be diluted with maximum 1 part clean water to 10 parts paint].</li> <li>Avoid painting in direct sunlight.</li> <li>Store the paint in a cool place.</li> </ul>
Recommended System:	<ul style="list-style-type: none"> <li>On new and bare surfaces prime with Oasis Acrylic Primer or Oasis Tex Primer.</li> <li>Apply 1 coats of Trushield Heritage Classique Textures</li> <li>Apply 1 or 2 coats of Trushield Heritage Silk.</li> <li>Apply 1 or 2 coats of Trushield Heritage Glaze.</li> </ul> <p>For best colour consistency use sufficient tinted / coloured paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.</p>



## Trushield Heritage Classique

Health, Safety and

Environmental Information:

- Keep out of the reach of children.
- If swallowed, seek medical advice immediately.
- Avoid contact with skin and eyes.
- Do not empty into drains.
- Ensure good ventilation during application and drying.
- Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Trushield Exterior Emulsions

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

