

## Trushield Heritage Glaze

Description:	Trushield Heritage Silk is high quality water based emulsion based paint designed for creation of artistic antique like effect on old and new surfaces alike.
Recommended Usage:	Ideal Glaze for exterior areas and withstands vigorous washing, it gives a smooth silk, antique touch to the surfaces
Pack Size:	1 Litre, 1 USG [3.78L], 5 USG [18.9L]
Physical properties:	
Finish:	Smooth, Silk
Colour range:	Limited Colours
Volume (Solids %):	35 ± 2%
Specific gravity:	1.20 ± 0.03
Theoretical spread rate:	14-18 m <sup>2</sup> /litre
Flash point:	Non-flammable
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will vary according to temperature, humidity and film thickness and will be affected accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Surface dry:	1-4 hours
Recoat window:	2-4 hours
Full dry:	24 hours
	The given data is meant to be considered as guidelines only. The actual drying time before recoat may vary according to atmospheric conditions at site.
Surface Preparation:	<ul style="list-style-type: none"> <li>• Surfaces must be clean, completely dry and free from defects, oil, wax, grease and dust. Any chalking or any loose flaking material must be removed by scraping or brushing with a stiff bristle brush.</li> </ul>
Application:	<ul style="list-style-type: none"> <li>• Stir thoroughly before use</li> <li>• Use brush, roller.</li> <li>• Thin with half part of clean water &amp; half part of Oasis Thinner: 36</li> <li>• Avoid painting in direct sunlight</li> <li>• Store the paint in a cool place</li> </ul>
Recommended System:	<ul style="list-style-type: none"> <li>• On new and bare surfaces prime with Oasis Acrylic Primer.</li> <li>• Apply 2 full coats of Trushield Heritage Texture.</li> <li>• Apply 1 coat of Trushield Heritage Silk.</li> <li>• Apply 1 or 2 coats of Trushield Heritage Glaze.</li> </ul> <p>For best colour consistency use sufficient tinted / coloured paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.</p>

Trushield Exterior Emulsions



## Trushield Heritage Glaze

Health, Safety and

Environmental Information:

- Keep out of the reach of children.
- If swallowed, seek medical advice immediately.
- Avoid contact with skin and eyes.
- Do not empty into drains.
- Ensure good ventilation during application and drying.
- Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Trushield Exterior Emulsions

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

