

Trushield Texcoat

Description:	Trushield Texcoat is a single pack emulsion based high build texture intermediate coating designed to give spatter finish. It can be over coated with other Trushield Smooth range products or Oasis Solvacryl and Oasis Polyurethane.
Recommended usage:	Recommended as an intermediate coating tile system for Interior and exterior masonry and plaster surface.
Pack Size:	1 USG [3.78L], 5 USG [18.9L]
Physical properties:	
Finish:	Texture
Colour range:	Off White
Volume (Solids. %):	62 ± 2%
Specific gravity:	1.76 ± 0.05
Theoretical spread rate:	1-2 m ² /litre depends on the texture
Flash point:	Non flammable
Drying Time: <small>(Single coat at standard thickness)</small>	Drying time will vary according to temperature, humidity and film thickness and will be affected accordingly e.g. the drying times quoted will be significantly longer in cold, damp conditions.
Surface dry:	1 hour
Recoat Window:	3-4 hours
	The given data must be considered as guidelines only. The actual drying time before recoat may vary according to atmospheric conditions at site.
Recommended System:	<ul style="list-style-type: none"> • On new and bare surfaces prime with 1 coat of Oasis Acrylic Primer • Apply 1 coat of Trushield Texcoat • Apply 2 coats of Trushield Smooth Range products or Oasis Solvacryl or Oasis Polyurethane <p>For best colour consistency use sufficient tinted / coloured paint for each job, including touch up. Advisable to maintain consistency of purchase from the same source.</p>
Surface Preparation:	<ul style="list-style-type: none"> • Surfaces must be sound, clean, completely dry and free from defects, oil, wax, grease and dust. Any chalking or any loose or flaking material must be removed by scraping or brushing with a stiff bristle brush. • Use suitable filler for smaller cracks and holes.
Application:	<ul style="list-style-type: none"> • Stir thoroughly before use • Use Special Hopper Gun. • Ready to use*[Depending on site conditions the paint can be diluted with maximum 1 part clean water to 10 parts of paint] • Avoid painting in direct sunlight • Store the paint in a cool place.
Advantages:	High build durable texture. Good hardness. Water resistance. Chemical resistance. Different texture can be obtained by varying film thickness by spray application

Trushield Exterior Emulsions



Trushield Texcoat

Health, Safety and
Environmental Information:

- Keep out of the reach of children.
- If swallowed, seek medical advice immediately.
- Avoid contact with skin and eyes
- Do not empty into drains
- Ensure good ventilation during application and drying.
- Dry sanding of the dry paint film will give rise to dust and/or hazardous fumes. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Trushield Exterior Emulsions

For more information refer to the product MSDS.

Disclaimer: Product warranty is based on our experience and test results and is independent of application defects, incorrect/improper usage and used in site conditions which are different from the recommended conditions mentioned in this data sheet. We reserve the right to change the data without prior notice.

