

TECHNICAL DATA

PRODUCT: OASISFLOOR SL2

Description : Oasisfloor SL2 is a two component solventless coating for decorative and industrial floor

Features :

- Solvent less coating
- Easy to apply by notch trowel
- Wide range of uses in different type of exposure condition
- Smooth, cleanable floor
- Excellent adhesion
- Provides long-lasting protection to concrete
- Can be used indoors or outdoors
- Good durability and appearance
- Can be top coated with epoxy or PU top coats
- Suitable for new or old concrete
- Oasisfloor SL2 is a spreadable self-leveling epoxy coating for concrete floor protection where a smooth cleanable floor surface is required.
- Oasisfloor SL 2 may be applied over a broad temperature range an average DFT of 2000 microns

Recommended use :

- Garages, car parks, car workshops Service stations,
- Loading ramps, Pedestrian walkways
- Aircraft hangers and maintenance areas
- Industrial and commercial warehouses
- Laboratory floors
- Pharmaceutical plants
- Automotive service station
- Power plants
- Waste water and sewage treatment plants

System Information

Selflevelling Smooth System	OASISFLOOR SEALER 8766	0.3-0.55KG/SQM
	OASISFLOOR SL2	1.9KG/SQM/1MM
Selflevelling Mortar System	OASISFLOOR SEALER 8766	0.3-0.55KG/SQM
	OASISFLOOR MORTAR	Approx 2.7 KG/SQM/MM
	OASISFLOOR SEALER 8766	0.3-0.55KG/SQM
	OASISFLOOR SL2	1.9KG/SQM/1MM

Colours : in desired shades

Volume Solids (%) : 99%±1

Flash Point : NA

March 2013
Issue 1: Revision:0



For further information please contact –
AL GURG PAINTS L.L.C
 Head Office & Factory – P.O. Box 22334,
 Sharjah, U.A.E
 Tel : (+971)6-5343919 Fax : (+971)6 343983
 E-mail : enquiries@agp.ae
 Web : www.aglpuae.com

TECHNICAL DATA

PRODUCT: OASISFLOOR SL2

Specific Gravity (Kg/Ltr)	:	1.8±2% (May vary with shade)
Mixing ratio	:	Base – 85 parts by Weight Additive – 15 parts by Weight
Pack Size	:	Base - 17 kg Additive - 3Kg
Pot Life	:	20-30 min
Drying time at 30 Deg C	:	Surface Dry 1hr Foot traffic 24hrs Vehicular traffic 7 days
Cleanser	:	OT 2
Application Notes	:	Suitable for application over suitable concrete sealer or epoxy Mortar
Application Methods	:	Notch trowel
Surface Preparation	:	Ensure surface to be coated are dry and free from all traces of surface contaminants

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION (READ THIS SECTION BEFORE USE)

SOLVENT BASED/SOLVENTLESS PAINT PRODUCT

- Ensure good ventilation during application and drying. Do not breathe vapour/spray.
- When applying by spray inside, wearing of air supplied breathing equipment will always be necessary. All respiratory equipment must be suitable for the purpose and meet an appropriate standard.
- When applying paint it is advisable to wear suitable eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove splashes from skin: use soap and water or a recognized skin cleaner.
- Keep container tightly closed and keep out of reach of children. Do not use or store by hanging on a hook.
- Do not empty into wadis, drains or watercourses.
- Contains no added lead, Mercury and Chromium containing compounds

This data is subject to change without notice. Please ensure you have the latest copy by checking with our Customer Service Department.

March 2013
Issue 1: Revision:0



For further information please contact –
AL GURG PAINTS L.L.C
 Head Office & Factory – P.O. Box 22334,
 Sharjah, U.A.E
 Tel : (+971)6-5343919 Fax : (+971)6 343983
 E-mail : enquiries@agp.ae
 Web : www.aglpuae.com